

LITHIUM CARBONATE, PRIME GRADE

CAS No. 554-13-2
 EINECS-No. 209-062-5

Formula Li₂CO₃

Application An odorless white powder that freely flows, with a relatively fine particle size, guarantees 98wt%. It is applicable to manufacture of a wide range of specialized applications including flux, frits, glass, and other ceramic products.

Appearance An odorless white, free-flowing powder

Product Specifications

Li ₂ CO ₃	%	98.0	min
Na	ppm	3000	max
Fe	ppm	10	max
Ca	ppm	3000	max
SO ₄	ppm	1500	max
K	ppm	1000	max
Cl	ppm	2000	max
Mg	ppm	2000	max
B	ppm	300	max
LOI (550°C)	ppm	0.7	max
Particle Size	D90 < 70 micron		

Molecular weight 73.89

Water solubility @ 20°C 1.3 wt%

Physical Description White granular solid or powder, odorless.

Toxicity/Safety Factor May be irritating to the eyes. Not significantly hazardous for industrial or commercial applications.
 Refer to the Material Safety Data Sheet (MSDS) for further information on toxicity and safety.

Transport Regulations	No regulations set forth in the RID, ADR, IMDG, and IATA-DGR.
Handling	Avoid contact with the eyes, skin and clothing. Ventilate the room well upon use. Wear protective glasses and rubber gloves. Wash hands thoroughly after use. Keep product away from strong acid.
Disposal	Dispose waste in accordance with both the local and federal laws and regulations.
Storage	Keep container closed.
Packing	500 kg big bags 1,000 kg big bags
Shipping Regulations	Lithium carbonate is not categorized under the hazardous class for shipping and transport. Shipments can be made either by air, sea, land, or rail in parcels as long as they meet the packaging terms and conditions of the carrier.
Labelling	Xn Harmful Xi Irritant R&S phrases see Material Safety Data Sheet

* The Primary grade lithium carbonate is not designed for and shall not be used for any drug use.